



Dayled 650

3200°K | 5600°K | DUAL COLOR

LTH 
Das Lichttechnikhaus Vertriebs GmbH

DAYLED 650

3200°K | 5600°K | DUAL COLOR

The DAYLED 650 units are the revolutionary LED fixture with Fresnel lens with high color rendering and high luminous efficiency.



Powered by a Powered of just 60W they generate a luminous output equivalent to approximately 650W. This fundamental and exclusive feature enables to avoid post-production interventions and allows a correct mixing with other light sources (like the sunlight).

The luminous intensity of the DAYLED 650 can be adjusted by the local Dimmer, placed on board the fixture or remotely via DMX control. In the manual adjustment, the digital display built in the fixture allows to visualize the luminous intensity at which the light is set. The units can be powered by mains or with practical and compact Li-ion batteries with long autonomy.

The extreme lightweight (weight is just 2.5 kg), along with the possibility to be powered with battery, make them particularly suitable, besides the use in video and TV studios, to an outdoor usage (interviews, production etc.).

SPECIFICATIONS

- » High color rendering index CRI>92
- » High TICI value (between 92 and 97)
- » 3200°K, 5600°K or variable from 3200°K or 5600°K
- » Super lightweight, compact and easy to handle (carbon fiber material, weight only 2.5 kg)
- » Power with battery or on mains
- » Heat-free
- » Continuously dimmable from 0 to 100% without variation of color temperature
- » Flicker Free Technology
- » Temperature detection LED sensor
- » Built-in DMX control
- » Instant restrike
- » Barn doors: 4 rotating included
- » Long life of LEDs
- » DAYLED 650 is also available with a pole operated yoke

	60W variable CCT COB LED, True colors'		60W
	Fixed colors: 10°-60° DualColor: 15°-50°		120 mm
	190 x 160 x 180 mm		2,5 kg

LTH - Das Lichttechnikhaus Vertriebs GmbH

Rudolf-Diesel-Str. 3
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0
Fax +49(0)82 21-20 79 8-69

Web www.lth-gmbh.de
E-Mail info@lth-gmbh.de